

## DECLARATION OF PERFORMANCE

No 9/A/KR/2018/EN

1. Unique identification code of the product type:

**System board KR/N-1G EPS 150**

2. Intended use/es:

**Product System board KR/N-1G EPS 150 is used in thermal insulation in construction**

3. The manufacturer:

**Kotar Sp. z o.o.**  
**ul. Kościuszki 33, 56-100 Wołów**  
Tel.: +48 71 389 23 16 Fax: +48 71 389 44 94 Email: kotar@kotar.pl

4. System or systems of assessment and verification of constancy of performance of the construction:

**System 3**

5. Harmonised standard:

**EN 13163:2012+A1:2015, „Thermal insulation products for buildings- Factory made expanded polystyrene (EPS) products- Specification.”**

6. Notified body/ies:

- Instytutu Techniki Budowlanej, Jednostka notyfikowana numer – 1488
- Polskie Centrum Badań i Certyfikacji , Jednostka notyfikowana numer - 1434
- Instytut Mechanizacji Budownictwa i Górnictwa Skalnego, Jednostka notyfikowana numer - 1454

## 7. Declared performance/s:

Table no.1

Essential characteristics	Clauses in this and European standard(s) related to Essentials characteristics	Regulatory classes/NPD <sup>1</sup>	Harmonised technical specification
Thermal resistance	Thermal resistance and Thermal conductivity	R <sub>D</sub> – ( Table no. 2) At most 0,035 W/m·K	<b>EN 13163:2012 +A1:2015</b>
	Thickness	T(2) (± 2mm) d <sub>N</sub> (Table no. 2)	
Reaction to fire	Reaction to fire	F	
Durability of reaction to fire against heat, weathering, ageing /degradation	Durability characteristics	NPD	
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance and Thermal conductivity	R <sub>D</sub> – ( Table no.2) At most 0,035 W/m·K	
	Durability characteristics	NPD	
Compressive strength	Compressive stress or Compressive strength	CS(10)150	
Tensile/Flexural strength	Bending strength	BS200 (≥ 200 kPa)	
	Tensile strength perpendicular to faces	NPD	
Durability of reaction to fire against heat, weathering, ageing /degradation	Compressive creep	NPD	
	Freeze-thaw resistance	NPD	
	Long-term thickness reduction	NPD	
Water permability	Long term water absorption by immersion	NPD	
	Long term water absorption by diffusion	NPD	
Water vapour permeability	Water vapour transmission	NPD	

### Kotar Sp. z o.o

ul. Kościuszki 33  
56-100 Wołów  
e-mail: kotar@kotar.pl  
[www.kotar.pl](http://www.kotar.pl)

tel. +48/71 389 23 16  
+48/71 389 44 94  
fax +48/71 389 44 94 wew. 21

Sąd Rejonowy dla Wrocławia-Fabrycznej,  
IX Wydział Gospodarczy Krajowego  
Rejestru Sądowego  
KRS: 0000708604  
Kapitał Zakładowy 1.100.000,00 zł

NIP: 917-000-27-93  
NIPUEPL9170002793  
Regon: 931615130  
KONTO BZ WBK SA 1 o/Wołów:  
62 1090 2460 0000 0006 2200 1593

Impact noise transmission index (for floors)	Dynamic stiffness	NPD	
	Thickness	NPD	
	Compressibility	NPD	
Continuous glowing combustion	Continuous glowing combustion	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD	

<sup>1</sup> NPD – No performance determined)

Table no.2: Declared thermal resistance  $R_D$  [ $m^2K/W$ ]:

Thickness [mm]	11	30
Declared Value [ $m^2K/W$ ]	0,30	0,85

Website address where is available this declaration of performance:

<http://www.kotar.pl>

The performance of the product identified above is in conformity with a set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (UE) no 305/2011 under the sole responsibility of the manufacturer identified above.

### Information provided with declaration of performance

1. Information referred to in article 31 of ordinance (EC) no. 1907/2006 (REACH)
  - Not applicable
2. Information about substances contained in the product specified in article 33 of ordinance (EC) no. 1907/2006 (REACH)
  - Not applicable

Name and signature of entitled person:

**Marcin Jaworski**

*(name and surname)*

**Wołów, 02.01.2018 r.**

*(place and date)*

*(signature)*

#### Kotar Sp. z o.o

ul. Kościuszki 33  
56-100 Wołów  
e-mail: [kotar@kotar.pl](mailto:kotar@kotar.pl)  
[www.kotar.pl](http://www.kotar.pl)

tel. +48/71 389 23 16  
+48/71 389 44 94  
fax +48/71 389 44 94 wew. 21

Sąd Rejonowy dla Wrocławia-Fabrycznej,  
IX Wydział Gospodarczy Krajowego  
Rejestru Sądowego  
KRS: 0000708604  
Kapitał Zakładowy 1.100.000,00 zł

NIP: 917-000-27-93  
NIPUEPL9170002793  
Regon: 931615130  
KONTO BZ WBK SA 1 o/Wołów:  
62 1090 2460 0000 0006 2200 1593